

Solar Frontlit Premium



SL-F02

Soyang's innovative eco range: PVC-Free. Low-emission.
Oekotex Standard 100 Certificated.

BRIEF DESCRIPTION

- PA-coated, 1000x1000, 20x20 base fabric
- Can be used as banners both indoors and outdoors

FEATURES



PVC-FREE



PHTHALATE FREE



LIGHT-WEIGHT



GOOD OPACITY

INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	280 g/sq.m	8.3 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060, ASTM D 1907	1100x1100 dtex	1000x1000 denier
Shielding Rate	ANSI PH2.19, ISO 5/2	83%	
Tensile Strength	DIN EN ISO 1421	2490x2230 N/5cm	285x255 lbs/inch
Tear Strength	DIN 53363	530x490 N	119x110 lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds
Storage Temperature		10 ~40°C	39~89°F
Storage Humidity		10~70%RH	
Shelf Life		12 months at recommended storage temperature and humidity	

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

