

Solar Reinforced Blockout



SL-BL02

Soyang's innovative eco range: PVC-Free. Low-emission.

Oekotex Standard 100 Certificated.

BRIEF DESCRIPTION

- 1000Dx1000D base fabric, high tenacity, better strength
- W/B/W structure makes it full opacity
- Anti-curling, excellent consistency on both sides
- Can be used as indoor hanging banner, roll up, display, curtain or short time outdoor pole banner, etc

FEATURES



PVC-FREE



PHthalate FREE



FULL OPACITY



FIRE-RESISTANT

INK PRINTABILITY



UV



LATEX



SOL



ECO SOL

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	380 g/sq.m	11.2 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060, ASTM D 1907	1100X1100 dtex	1000x1000 denier
Shielding Rate	ANSI PH2.19, ISO 5/2	100%	
Tensile Strength	DIN EN ISO 1421	2500x2350 N/5cm	286x269 lbs/inch
Tear Strength	DIN 53363	380x370 N	85x83 lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds
Storage Temperature		10 ~40°C	39~89°F
Storage Humidity		10~70%RH	
Shelf Life		12 months at recommended storage temperature and humidity	

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.