Solar Silky Greyback Frontlit



SL-F05

Soyang's innovative eco range: PVC-Free. Low-emission.

Oekotex Standard 100 Certificated.

BRIEF DESCRIPTION

- 100% polyester woven fabric coated with grey back
- Smooth surface, full opacity
- Can be used as wall covering in home deco, also as banner, roll-up for indoor & short-time outdoor

FEATURES











INK PRINTABILITY









MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	270 g/sq.m	8 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	
Yarn Dtex	DIN EN ISO 2060, ASTM D 1907	330x330 dtex	300x300 denier
Shielding Rate	ANSI PH2.19, ISO 5/2	100%	
Tensile Strength	DIN EN ISO 1421	1800x1200 N/5cm	206x137 lbs/inch
Tear Strength	DIN 53363	265x120 N	60x27 lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds
Storage Temperature		10 ~40°C	39~89°F
Storage Humidity		10~70%RH	
Shelf Life		12 months at recommended storage temperature and humidity	

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.







