Solar Greyback Frontlit Apex

SL-F08

Soyang's innovative eco range: PVC-Free. Low-emission.
Oekotex Standard 100 Certificated.

BRIEF DESCRIPTION

- 100% polyester woven fabric with grey coated back, PVC-free and truly eco-friendly
- Outstanding surface whiteness for more vibrant color reproduction
- 5m max width, perfect opacity for seamless wall coverings
- Excellent curl resistance and low fuzzing under repeated pulling
- Also ideal for roll-up, frontlit banner, roller curtain, art decoration, etc

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	290 g/sq.m	8.6 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100% Polyester	
Yarn Dtex	DIN EN ISO 2060, ASTM D 1907	330x660 dtex	300x600 denier
Shielding Rate	ANSI PH2.19, ISO 5/2	100%	
Tensile Strength	DIN EN ISO 1421	1640x1742 N/5cm	187x199 lbs/inch
Tear Strength	DIN 53363	233 x215 N	52x48 lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds
Storage Humidity		10~70%RH	
Shelf Life		12 months at recommended storage temperature and humidity	

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

SOYANG
www.soyang.net

ISO 9001

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100
20.HCN.12564 HOHENSTEIN HTTI

Global Recycled Standard